



# C800 series - Grade 3 - Cylindrical leverset

## SPECIFICATIONS :



Exposed trim - Levers are made of zinc die casting, roses are made of stainless steel or brass

Keying - 5 pins tumbler SC1 keyway with three brass silver nickled plated keys, 6 pins are available for master keying or as option.

Housing : Wrought steel housing with chromated finish for better corrosion resistance.

Backset: universal 2-3/8"(60mm) back, and 2-3/4"(70mm) backset available.

Finish : PVD finish lasting 480 hours salt spray test and 96 hours for standard finish

Cycle passed - 200,000 cycle passed meets ANSI A156.2 grade 3

Door thickness : 30-50mm door thickness, option upto 55mm



**C803-10-PB**

## FINISHES

CODE	AB	AC	PB	SB	ORB	PVD
BHMA	609	616	605	606	613	505
US	5	11	3	4	10B	11P



CODE	SS	PS	CP	SC	AN	SN
BHMA	630	632	625	626	620	619
US	32D	32	26	26D	15A	15



## FUNCTION



**00**  
Unlocked by key from outside when outer knob/lever is locked by turn-button in inside knob/lever

**10**  
Turn-button locking. Unlocked from outside by turning emergency turn- button

**30**  
Both knob/lever always unlocked

**50**  
Unlocked by key from outside, inside knob/lever always free.

**60**  
Lock or unlock by key outside, inside always free

