

GN200-6401-MB



Heavy Duty US Mortise Lock



SPECIFICATION

Finish Available:	US3, US4, US5, US15, US26, US26D, US10B
Deadbolt:	1"(25mm) throw 2 pcs. Hardened steel rod
Latch Bolt:	Standard 3/4"(18mm) x 1"(25mm) extension throw
Latch Backset:	STD. 64mm, OPT. 70mm, 90mm
Latch Face Plate:	Square cornered 1-3/8"(32mm) x 8 1/4"(204mm)
Strike:	Half lip strike 1-7/8"(47mm) x 4-3/4"(119mm)
Cylinder and Keys:	M=solid Brass Dimple cylinder with 3 nickel plated keys N=solid Brass traditional cylinder with 3 nickel plated keys
Handing:	Left / Right handed
Door Thickness:	Standard: 1-5/8"(38mm) to 2"(51mm) Option: 2"(51mm) to 2-3/8"(61mm) Specify when order

COMPLETE WITH: 64 OR 70MM BACKSET, U.S. MORTISE LOCK CASE GRAB HANDLE SET IN EXTERIOR MORTISE THREADED CYLINDER SCREW PACK & DECORATED COVER PLATE LEVER OR KNOB, 8X8MM SPLIT TYPE SPINDLE KNOB WITH 4MM SPINDLE

