



TUBULAR DEAD BOLT LOCK D2800

SPECIFICATIONS :

Exposed trim - Levers are made of zinc die casting, roses are made of stainless steel or brass

Keying - 5 pins tumbler SC1 keyway with three brass silver nickled plated keys, 6 pins are available for master keying or as option.

Housing : Wrought steel housing covers with brass or stainless steel

Backset: universal 2-3/8" (60mm) back, and 2-3/4" (70mm) backset available.

Finish : PVD finish lasting 480 hours salt spray test and 96 hours for standard finish

Cycle passed - 200,000 cycle passed meets ANSI A156.2 grade 2

Door thickness : 30-50mm door thickness, option upto 55mm



FINISHES

CODE	AB	AC	PB	SB	ORB	PVD
BHMA	609	616	605	606	613	505
US	5	11	3	4	10B	11P





CODE	SS	PS	CP	SC	AN	SN
BHMA	630	632	625	626	620	619
US	32D	32	26	26D	15A	15



HOW TO ORDER

BRAND	SERIES	FUNCTION	FINISH
MP	D2800	01	US32D



SINGLE CYLINDER	01
DOUBLE CYLINDER	02

ANSI	E2152	E2142
Description	Deadbolt thrown or retracted by key outside / thumbturn inside.	Deadbolt thrown or retracted by key either side.