



Alarm Exit Hardware

MP-7000-AVS-28/36/48 Vertical Rod Panic Exit Device
 MP-7000-AVF-28/36/48 Vertical Rod Fire Exit Device



CONFORMS TO STANDARDS
 UL 10C AND UBC 7-2 (1997)

Specifications

- For Doors-----1-3/4" thick standard optional 2-1/4" thick. 4-1/2" minimum stile width required for single or double door application using standard 239 strike and pull or lever trims
- Chassis-----Nonferrous alloy (Panic Grade), steel (Fire Grade).
- Cover -----Nonferrous alloy. Cover stock hollow metal doors with 161 cutout.
- Mounting ----- Furnished standard with wood and machine screws. Available with thru bolts on request.
- Alarm ----- Available. Prefix "Alrm" before part #.
- End Cap ----- Steel construction.
- Hand ----- Easily field reversible. Specify at time of order LHRB, RHRB for convenience.
- UL and ULC Listed --7000Series for fire exit hardware for all types of 8' x 8' double doors for up to 3 hours fire labeled installations, conforms to standards UL 10C and UBC 7-2-1997 codes.
- Dogging Feature ----Allen-type key furnished standard on non-fire labeled devices.
- Finish ----- Aluminum(alum), dark bronze duranodic (duro), gold.
- Rail Assembly -----Heavy gauge steel, painted.
- Latch Bolt, Spring ---Stainless steel.
- ANSI standard ----- A156.3, Grade 1.
- Rail Assembly----- Heavy gauge steel, painted.
- Door size ----- 36" x 84" / 48" x 96" / 36" x 96" doors.



MP-7000-AVF-36-US32D

Dimensions

Touchbar height to finished floor	41"(1043mm) at center
Touchbar projection	
neutral	2-1/2"(64mm)
depressed	1-3/4"(45mm)
Device length - short 3' (914mm)	5-1/8" x 2-3/4" x 2" (129mm x 68mm x 52mm)
long 4' (1219mm)	2'9" x 3'(840mm to 914mm) door size
	2'9" x 4'(1145mm to 1219mm) door size
Panic grade top latch case	3-15/16" x 2-1/8" x 1-3/8"(100mm x 52mm x 42mm)
Fire grade top latch case	3-15/16" x 2-11/16" x 2-1/16"(100mm x 68mm x 53mm)
Top rod length for 36" x 84" do	Top rod 43-1/4" (1100mm)
Top rod length for 48" x 96" do	Top rod 53-1/16"(1350mm)
	1/2"(13mm) Round tubing.

